



NIPOSEAL

Bitu Sealing Compound

A solvent-borne, thick black Bituminous Compound formulated with specially selected fibre, for a semi stiff paste.

It provides a soft and flexible bond which hardens and softens with changes of temperature.

Drying time will vary depending on weather conditions and time. This allows the compound to develop a tack.

It has been observed that indoor/concealed applications have resulted in the material remaining soft.

All heavy applications will result in extended drying time.

ADVANTAGES

- Does not require a primer
- Maintains a viscous jelly state permanently
- Strong creep performance
- Easy to handle
- Self-healing
- Anti-leaking
- Anti-fatigue
- Stress-free
- Cold-applied
- Immediate ponding
- In-can long shelf life
- Free from asbestos
- Can be applied on non-porous substrates
- Protects against rust
- Sound/Vibration dampening

APPLICATION

Substrates should be sound and clean (from dust, loose particles, oil and grease).

Apply using a spatula/scrapper directly from the pail.

Whilst every effort is made to ensure that the contents of this material is accurate and current, it is the user's responsibility to satisfy itself of the suitability of products for its own particular purpose. As the actual use by others is beyond our control, we do not provide any guarantee, implied or expressed, as to the effects of such use. No liability is accepted by Nipo International Pte Ltd, its staff and/or its distributors, for any loss or damage, direct or indirect, that may result from using the product, information or adopting recommendations and/or suggestions as actual conditions for use are beyond our control. This information is not to be construed as absolutely complete since additional information may be necessary or desirable for exceptional or particular circumstances.

Dated July 2020

Protect sides of joint or application area with masking tapes to avoid paint-over.

- For Horizontal Cracks and Joints (including Expansion Joints)
 - a. Clean the surface by brushing or wiping with a piece of rag
 - b. Fill up the crack with *NIPOSEAL* using a knife or a trowel.
 - c. Ensure material fully covers the crack/joint
 - d. Where required, conceal and protect the Compound with metal flash strips or backer rod
- For Holes and/or Overlays/Overlaps on Roofing Sheet
 - a. Clean the surrounding of the hole/overlay off any dust or loose material
 - b. Apply a coating of *NIPOSEAL* around the hole/overlay
 - c. Cover the hole with a piece of *GLASSFIBRE NETTING*.
 - d. Paint over the *GLASSFIBRE NETTING* with *NIPOSEAL*
- For waterproofing and sealing of corrugated iron and asbestos roof.
- For the repair of leaks and cracks in all kinds of roofs.
- For rejuvenating old felt roofs, zinc or asbestos roofs.
- For the protection of the under-carriage of vehicles.
- Not suitable for UV exposure
- Do not use in conjunction with water based emulsions



NOHARA

Exclusive Partner in Vietnam
NOHARA INTERNATIONAL
Representative Office Ho Chi Minh City

NOHARA CARE
T: +84 916 282 875
E: vietnam@nohara-inc.co.jp
W: nohara-international.com



SPECIAL NOTES

Air exposed material may become too viscose to handle:

- Ensure pail is properly covered and secured.
- Leave the closed pail outdoor under the very hot sun for several hours.
- This may facilitate softening of the material for easier handling.
- An oily shiny film may be evident during this exposure.
- Agitate with a strong power drill till homogeneous.
- Always keep material properly covered.



TECHNICAL SPECIFICATION

TYPICAL PROPERTIES	
Theoretical Solid Content	At least 85%
Flash Point	>30°C
Colour	Black
Specific Gravity	Approx 1.25
Nett Weight (pail)	Approx 25Kg/20L
Usage : W2.5cm X H2.0cm X L100.0cm	0.65kg to 0.80kg per 500cm ³

Whilst every effort is made to ensure that the contents of this material is accurate and current, it is the user's responsibility to satisfy itself of the suitability of products for its own particular purpose. As the actual use by others is beyond our control, we do not provide any guarantee, implied or expressed, as to the effects of such use. No liability is accepted by Nipo International Pte Ltd, its staff and/or its distributors, for any loss or damage, direct or indirect, that may result from using the product, information or adopting recommendations and/or suggestions as actual conditions for use are beyond our control. This information is not to be construed as absolutely complete since additional information may be necessary or desirable for exceptional or particular circumstances.

Dated July 2020



Exclusive Partner in Vietnam
NOHARA INTERNATIONAL
 Representative Office Ho Chi Minh City

NOHARA CARE
 T: +84 916 282 875
 E: vietnam@nohara-inc.co.jp
 W: nohara-international.com