

DESCRIPTION

BituPrimer is a solvent-borne bituminous emulsion designed to penetrate and seal porous surface. BituPrimer seals and prepares the surfaces of many substrates including concrete, asbestos cement, lightweight concrete screeds and asphalt concrete. Its good bonding properties ensure good adhesion to substrate when applied; at least one of the substrate must be porous in order to achieve a good cure.

COMPLIED STANDARD

- TCVN 9065: 2012

AVANTAGES

- Non-toxic
- Anti corrosive
- Economical
- Cold applied



RECOMMENDEND TO USE

Seals and prepares substrates for subsequent application. Used as a primer coat prior to the application of torch applied and liquid applied bituminous waterproofing membranes. Water repellent coating to bathroom, planter boxes, roof, gutters, downpipe, flashings.

EXCUTION METHOD

The application procedures may vary slightly depending on site conditions. The general recommended guidelines for the bitumen coating is as follows:

Surface to be applied must be dry and clean; free from dust, dirt, grease, moss, lichen or any other foreign matter.

SPECIFICATIONS	
Form Relative Density	Liquid Emulsion
Colour	Dark Brown
Solid Content	Approximately 40%
Application Temperature 5 to 45 0C	1h
Touch Dry	1.5 to 2 hours
Fully	7 days
Cure Peel adhesion-toconcrete (primer with Self Adhesive Membrane) KN/m width	2.2

DRYMAS VIETNAM CO., LTD

Head Office 1st Floor, X2 Building, Lane 34, Nghia Do Street, Tay Ho District, Hanoi
 Website: www.drymas.vn Email: info@drymas.vn
 Hotline: (024). 73013789

Factory Pham Van Dong Street, Cao Minh Village, Phuc Yen City, Vinh Phuc Province